



Android Operation Brings the Next Generation of Productivity and Efficiency

Visible LED indicators represent scanning result status, wireless connection, charging level and more.

RK95 series

4.3" touch display ensures readability and future adoption of touch-based applications.

28/38/52 keypad options. Terminal Emulation keypads support TN and VT systems.





Optional 13 MP camera embedded with specific angle to prevent it from being blocked by user's hand while gripping pistol or taking photos.



IP65

2x2 MU-MIMO technology with increased data capacity and transmission speed.

Versatile reader options of laser, 2D imager, mid-range 2D imager, and extended-range 2D imager fulfill different user demands in reading distance.



barcode reading over 21 meters

In-house curved shape makes it easy to grip.



Lightweight and pistol designs to guarantee all-day comfortability.

3000 6000 6000

Two battery options with hot-swappable and easy-removable features allow one-hand operation.

Operation temperature down to -30°C



Comes with temperature sensor and heater control software allows user to automatically turn on/off heater based on surrounding environment. For example, set to turn on heater under -10°C and turn off above 20°C.

- Heaters embedded in touch screen and scan window to ensure fog-free display and frost-free scanning.
- Ice-resistant materials built into the product itself to prevent potential damage caused by prolonged operation in low temperature environments.
- Freezer 5,500 mAh battery optimized for low temperature environment, min. 5 working hours at -30°C.







Android Operation Brings the Next Generation of Productivity and Efficiency

CipherLab's RK95, the next generation of the 9700, brings the productivity and efficiency to the next level. Its advanced mobile computing platform and superior wireless options extend performance in the warehouse environment. With the latest Android operating system, the RK95 has fulfilled larger data collection with multiple keypad options and intensive scanning usage with versatile reader options. It not only fulfills traditional users' legacy warehouse applications but also new applications from indoors to outdoors.

Accurate and Upgraded Features with **Google Certification**

CipherLab's RK95 is a powerful handheld terminal that steps up the data collection game in the warehouse environments. Data processing is made fast and easy with a powerful processor. Modernized terminal emulation and physical keypad options make data collection easy for legacy and new users. Along with Google certification, the RK95 is a powerful handheld terminal that enhances workforce productivity and daily operations. Superior Wi-Fi coverage keeps multiple workers connected simultaneously, while 4G/LTE supports new applications from indoors to out. Its powerful and upgradeable mobile computing platform operates with higher standards and security. With durable designs and resourceful data capture, the RK95 is surely an investment that is smart and cost effective for your business.



Superior Performance with Advanced Certified Mobile Computer Platform

CipherLab RK95 is powered by the octa-core 2.2 GHz processor with 4 GB RAM/64GB Flash memory. Your staff can process the data in an instant without any interruptions. Moreover, its latest Android 9.0 operating system is upgradeable to one later version. The RK95's intuitive interface allows your staff to have less training and access the most up-to-date Android applications. It is also certified by Google's GMS and AER programs to ensure applications operate smoothly with elevated standards. Regular

guarterly security updates are guaranteed for five years after its launch. Zero-touch enrollment with AER makes large scale Android deployment across multiple devices simple.



Reliable Transmission Increases Workforce Productivity

The RK95's reliable transmissions include IEEE802.11 a/b/g/n/ac of dual band and MIMO 2x2 technology. With MIMO 2x2, the RK95 offers superior Wi-Fi coverage and high-speed data throughput that keeps multiple workers connected simultaneously. With the ability to fast roaming in 1 seconds and reconnect in 7 seconds, the RK95 can handle big data transmission without disturbances. Workers can enjoy a more reliable wireless network regardless of location without interferences.

Durable Designs that Outlast a Full Shift

The CipherLab RK95's IP65 rating, 1.8 m drop resistance and 1,000 tumbles at 1 m help support productivity with full protection from water, dust and accidental drops. Workers can feel secured when they work, knowing RK95's Corning Gorilla Glass improves damage resistance and toughness against chips and scratches. The keypad, with quality printing, also passed a durability test of 1 million presses. The RK95 can even extend its productivity into the cold storage or freezers and prevent device condensation. Along with all that durability, workers can operate for more than 8 working hours with the hot-swappable 3,000 mAh or 6,000 mAh battery, and more than 5 working hours with freezer battery.





Resourceful Data Capture

CipherLab RK95's versatile reader options, laser, 2D imager, mid-range 2D imager and extended-range 2D imager, give you long distance barcode reading capabilities from 7.6 cm to over 21.4 meters. The RK95 has the same great modularity of the 9700 series for easy field replacement and on-site services. Additionally, it has the new LED indicator for good or bad scanning. Workers can also capture detailed photos for records of the cargo conditions and the verification process with its optional 13 MP camera. RK95's NFC ability, available on request, helps to read NFC smart tags or emulate contactless cards for access control.

Easy Data Collection with Modernized Terminal Emulation and Physical Keypads

CipherLab RK95 provides a 38-key numeric and 52-key alphanumeric physical keypad option with CipherLab Terminal Emulation compatible with VT and TN systems. Additionally, the RK95's touch base operation can also support Android intuitive and interactive applications. Maximize simplicity with your choice of keypads or touch input for Terminal Emulation/Android Apps now or in the future. The RK95's 4.3-inch WVGA display also increases the readability and viewing area for your staff. It provides the best in-class indoor/outdoor readability and data input flexibility. Users can interact with the screen, regardless of the display is wet, with a finger, gloves or a stylus.

Elaborate Utilities and Software Solutions

CipherLab's RK95 supports more than just 3rd party software. It also supports CipherLab self-developed software utilities to boost your operation.

- / With CipherLab ReMoCloud[®], certified by Google EMM (Enterprise Mobility Management), provides solution to manage CipherLab's Android devices via internet anytime and anyplace. Supported by Google Zero-touch enrollment, ReMoCloud[®] allows administrators to track, monitor and manage applications from a central administrated area.
- / CipherLab Terminal Emulation supports systems of VT, TN3270 and TN5250 with full screen operation for efficient inventory management. With intuitive user interface, Wi-Fi status, battery capacity and custom font size/color, your business will undoubtedly save time and energy. Additionally, the Button Assignment which allows function key configuration will speed up the work process.
- / CipherLab ADC (Android Device Configurator) makes customized configuration and project setting easy for administrators. These configuration utilities can perform system updates over USB connection or WMDS (Wireless Mobile Deployment System). Through BarcodeToSetting, you could even facilitate mobile settings by scanning 1D/2D barcodes.









ANDROID 9.0		Call Startes	IP65	1.8M MULTIPLE DROPS		Extended Range	Mid-Range	NFC		1 2000 NUMERIC KEYPAD	
----------------	--	--------------	------	---------------------------	--	-------------------	-----------	-----	--	-----------------------------	--

	Operating System	Android 9 (GMS, AER certified with one later version upgradeable capability)			
	CPU	Octa-core over 2.2 GHz			
	Memory	64GB FLASH / 4GB RAM			
	Expansion	Micro SD Slot With SDHC (up to 32 GB) and SDXC (up to 2TB) Support			
Performance	Operating Power	Standard: Rechargeable 3.7V, 3000 mAh / 6000 mAh Li-ion Battery Cold Storage: Rechargeable 3.7V, 5500 mAh Li-ion Battery			
	Working Hours ²	Standard: Min. 8 working hours (3000 mAh), Min. 12 working hours (6000 mAh) Cold Storage: Min. 5 working hours at -30°C			
	Alert	LED indicatores for RF, charging status, scanning status (2 circular LED at front and 2 rectangle LED at sides) / Vibrator / Speaker			
	Interface Supported	USB 2.0 with OTG			
	WLAN	IEEE 802.11 a / b / g / n / ac / e / d / h / i / r / k / v / w , IPv4, IPv6, 2x2 MU-MIMO			
Wireless Communication	WLAN security	WEP, WPA (PSK, TKIP), WPA2 (AES, PSK), WPA-1X (TKIP,EAP-TLS, PEAP), WPA2-1X (AES, EAP-TLS, PEAP), 802.1x (EAP-TLS, PEAP) AES-CCMP, WPI-SMS4, WPS2.0, WAPI, EAP-TTLS (PAP, MSCHAP, MSCHAPv2), PEAPv0-MSCHAPv2, PEAPv1-EAP-GTC and LEAP, EAP-PWD			
	WPAN	Class 2 Bluetooth® v5.0 with BR / EDR and Low Energy (BLE) Support			
	Bluetooth [®] profile	GAP, SDAP, HSP, SPP, GOEP, OPP, HFP, PAN, A2DP, AVRCP, GAVDP, HID, PBAP			
	Barcode Scanning	Standard: Laser / 2D Imager/ Mid-Range 2D Imager / Extended-Range 2D imager / DPM¹ Cold Storage: 2D Imager/ Mid-Range 2D Imager / Extended-Range 2D imager / DPM¹			
Data Capture	Camera (Optional)	Autofocus 13 Megapixels with LED flash			
	NFC ¹	Supports ISO14443A, ISO14443B, ISO15693, Felica (Peer-to-Peer, Card Reader, Card Emulation)			
Physical Characteristics	Display	4.3" WVGA color display, Capacity Touch supports bare / wet / gloved finger and stylus inputs, Corning Gorilla Glass			
	Interactive Sensor Technology	Light sensor, Proximity sensor, Motion sensor, E-compass, Gyroscope, Temperature sensor for Cold Storage			
	Keypad	28-Key Numeric, 38-Key Numeric/Function keypads, 52-Key Alphanumeric keypads, Terminal Emulation keypads (TN5250, TN3270 and VT) ,with LED backligh			
	Voice and Audio	PTT voice ; Speaker, Microphones with noise reduction and echo cancellation, Bluetooth® headset			
	Size (LxWxH)	216 mm x 80 mm x 30 mm			
	Weight	Standard: 400 g (3000 mAh) / 445 g (6000 mAh), with 2D imager / 435 g (3000 mAh) / 480 g (6000 mAh), with Extended-Range 2D imager Cold Storage: 485 g, with 2D imager/ 520 g, with Extended-Range 2D imager			
	Operating temperature	Standard: -20°C to 50°C / -4°F to 122°F Cold Storage: -30°C to 50°C /-22°F to 122°F			
	Storage Temperature	-30°C to 70°C / -22°F to 158°F			
	Humidity (Non-Condensed)	Operating 5% to 95% / Storage 5% to 95%			
User Environment	Impact Resistance	IP65 / 1000 (1 m) Tumbles Standard: 1.8 m / 2.4 m with Rubber Boot, multiple drops onto concrete (MIL-STD-810G), crossing operating temperature Cold Storage: 1.5 m multiple drops onto concrete (MIL-STD-810G), crossing operating temperature down to -30°C			
	Electrostatic Discharge	± 15 kV Air Discharge, ± 8 kV Contact Discharge			
	Regulatory Compliance	FCC / BC / CA65 / SRRC / CCC / NCC / BSMI / CE / WEEE / RoHS / REACH / Erp / BISWPC / IC / NrCAN / RCM (the regulatory compliance for WWAN model is available on request, NRE and MOQ may apply)			
Development Support	CipherLab API and Android 9 Standard API				
Application Software	CipherLab: ReMoCloud®, Wireless Mobile Deployment System (WMDS), Android Device Configurator (ADC), BarcodeToSetting, AppLock, Button Assignment, Reader Configuration, Signature Capture, Airlock Browser, Mirror Terminal Emulation, Software Trigger Third Party: SOTI MobiControl, Xamarin Binding, iVanti Velocity Terminal Emulatior & Browser, AirWatch, Kalipso				
Accessories	Snap-on Cable (USB), Pistol Grip, Rubber Boot, 4-slot Battery Charger, 5-slot Terminal Charging Cradle, 20-slot Battery Charger Multi-slot Charging Cradle with Battery Charger, Charging and Communication Cradle, Hand Strap, Belt Holster for Device with Pistol Grip, Please contact us for availability: 5-slot Terminal Ethernet Cradle ¹ , Vehicle Cradle ¹				
Warranty	1 year				

1. Please contact us for availability.

2. Minimum 8 hours. 2D imager scanning per 20 seconds, LCD 50% backlight and speaker on (volume is default) at 25°C, Bluetooth® off / IEEE 802.11 a / b / g / n / ac on. The test is based on one broadcasting packet per second.

ACCESSORIES



(USB)

Communication

Cradle







Battery Charger



Multi-slot

Charging Cradle with Battery Charger



20-slot Battery Charger



©2021 CipherLab Co., Ltd. All specifications are subject to change without notice. All rights reserved. All brand, product and service, and trademark names are the property of their registered owners. TRK95X0101501 - 06/2021