

......



4G 📣 🗎 🌔

SUNDAY, OCTOBER 1







Slim and compact



Efficiency, Versatility and Slim Design for Competitive Advantages



CipherLab's RS35 is the device that brings enterpriseclass features through a pocketable consumer style smartphone with rugged designs. The RS35 focuses on the versatility of its features, and it aims to provide its users the ability to deliver a positive customer experience, offer more convenient service and save time and effort. With its versatile features, the RS35 gives businesses competitive advantages that help the mobile workforce get more work done in less time.

An Affordable Device that is Versatile and Intuitive

CipherLab's RS35 is a versatile mobile device that provides your enterprise and staff a better solution for daily tasks with efficiency. If you're looking for device that can streamline workflow with the combination of integrated scanning, powerful processing, intuitive touchscreen interface and robust connectivity, the RS35 has got you covered. If manageability and enterprise-class security is your cup of tea, the RS35 has CipherLab's self-developed enterprise management tools for easy deployment and top data protection. CipherLab's RS35's competitive price combined with competitive features makes it the best investment for your business.



Data Capture with Agile Performances

CipherLab RS35's versatile reader options include 1D and 2D barcode scanning, HF RFID capabilities and contactless NFC application. Supported with agile reading, the RS35 can read barcodes even in poor condition. The three modes of NFC (card emulation, card reader, peer to peer) makes reading data effortless. It also comes with a switch button for UHF RFID reader so it's easy to switch modes for specific tasks. The RS35 UHF RFID reader, supporting the EPC Global Gen2v2 standards, has an excellent high-speed reading rate of more than 900 tags. Providing the best in class performance, it is available with software utilities including RFID Android SDK, EZConfig, and EZEdit. In the case of needing dierent reading angles, CipherLab's RS35 also provides the 70-degree tilting device on request.



Protection Against Accidental Drops and Demanding Environments

The CipherLab RS35's efficient features are under maximum protection with its rugged designs. RS35's rugged design keeps your workers free of worries when working in different environments. Its IP65 and IP67 ratings allow the device to work in demanding environments such as rain and dust. Furthermore, the RS35 has a 1.5m drop resistance, 1.8m drop resistance with rubber boot and 500 tumbles at 0.5m. Workers can feel completely secured while focusing on the tasks at hand. Its intuitive touchscreen is also protected with Corning Gorilla Glass, which is shatterproof and has a high resistance to scratches from sharp objects. With wide operating temperatures, the RS35's productivity is guaranteed in a wide range of environments and conditions. Additionally, its reliable designs can save repair costs and extend the life of the RS35.



Instant Access to Online Information with Seamless Wi-Fi Connection

The RS35 provides seamless in-store communication with one of the most reliable transmission solutions in the market. The RS35's transmission comes in the form of IEEE802.11 a/b/g/n/ac/d/h/i. These reliable connections support fast roaming and strengthen store operation in any industry. Its VoLTE feature with noise reduction microphone and echo cancellation assures easy in-store communication in any retail environment. With accurate route planning being so important in optimizing customer experience, RS35's GPS/A-GPS gives you accurate navigation across boundaries which is no doubt a convenient feature for last-mile delivery and light transportation & logistics.

Dependable Performance that is Long-lasting

The RS35 takes pride in its dependability in increasing user work efficiency with its powerful performances. It is equipped with Android 10/Android 11, Google Mobile Service (GMS) and the seal of Android Enterprise Recommended (AER) which give you full enjoyment of Google applications and consistent user experiences, and allow IT staff to manage Android devices with ease. Its Octa-core 1.8 GHz CPU has enough power to handle all your workload. With 3GB RAM/32GB ROM and an option to expand, the RS35 provides plenty of space for applications and data storage. CipherLab knows that your productivity heavily depends on our mobile device; therefore, our standard, removable and rechargeable battery can deliver an impressive 12 hours of power and ensure productivity for a full work shift. This removable 4000 mAh battery design can also reduce battery changing time, lower repairing cost and increase the device's life cycle. Moreover, the RS35 comes with a hot-swap feature that the dead battery can be simply replaced with a fully charged one even without leaving your current applications or switching to suspending mode. The unfavorable interruption and data loss is eliminated.



Intuitive and User-friendly Experience with User-centric Designs

User-centric design is very important when it comes to the RS35. This design, very similar to a smart phone, allows the users to feel familiar with the device and lessen the learning time. It features a large 5.5-inch screen which allows users to see more information clearly and avoid input mistakes. Moreover, users can see the screen without any problems indoors and outdoors with its 720x1,440-pixel IPS LCD screen. Its multi-touch panel supports wet, gloved fingers and stylus for users to use in different environments and applications. All these features are designed to be slim and lightweight so it's easy for anyone to carry.

Comprehensive Management Solutions



CipherLab ReMoCloud[®], certified by Google EMM (Enterprise Mobility Management), allows you to deploy, manage and monitor CipherLab's Android devices via internet anytime and anyplace from the comfort of one centralized location.



CipherLab ADC (Android Device Configuration) gives your administrator the ability to synchronize device settings and configurations with ease. These configuration utilities can perform system settings and updates over USB connection or WMDS (Wireless Mobile Deployment System). Through BarcodeToSetting, you could generate barcodes for the setting deployments.





ANDROID 10/11	1.5M MUTIPLE DROPS		SAM	802.11 a/b/g/n /ac	LTE
------------------	--------------------------	--	-----	--------------------------	-----

Performance Exp SIM Ope Wor Aler	perating System PU emory pansion	Octa-cor 32GB Flash	/Android 11 (GMS) re 1.8GHz			
Performance SIM Ope Wor Aler	emory	Octa-cor 32GB Flash	re 1.8GHz			
Performance Exp SIM Ope Wor Aler	,					
Performance SIM Ope Wor Aler	pansion	32GB Flash / 3GB RAM 64GB Flash / 4GB RAM				
SIM Ope Wor Aler		Micro SD card slot with SDHC (up to	32GB) and SDXC (up to 2TB) support			
Won Aler	M / SAM	2 SIM slots and 1 SAM slot	1 SAM slot			
Aler	perating Power	Replaceable and recharge	able 3.85V, Li-ion 4000mAh			
Aler	orking Hours ¹	minimum 12 hours				
	0	1 tri-color LED, 1 bi-color LED, vibrator				
Inte	erface Supported	6-pin I/O & USB 2.0 Type-C with OTG				
	WAN	EDGE/GPRS/GSM : 850/900/1800/1900 UMTS/HSPA+ : B1/82/84/ 85/86/88 FDD LTE : B1/82/ 83/84/85/87/88/812/ B13/817/819/820/825/826/828 TDD-LTE : 38/39/40/41 Support VoLTE and Worldwide Band	_			
WLA	LAN	IEEE 802.11 a/b/g/n/ac/d/h/i				
Add	ditional WLAN Features	802.11r (fast roaming), 802.11 v / k (Voice-Enterprise), CCX (Cisco Compatible Extensions) compatible				
WP	PAN	Bluetooth® Class I, V4.2 dual mode,	V2.1 with Enhanced Data Rate (EDR)			
GPS	°S	GPS / A-GPS / GLONASS / Galileo / Beidou	-			
Baro	rcode Scanning		er (SE4770)) tilting angle at 70°²			
Data Capture RFIE	ID Read / Write	HF RFID 13.56 MHz frequency which supports ISO14443A, ISO14443B, ISO15693, and Felica Support NFC (Peer-to-Peer, Card Reader, Card Emulation)				
Can	mera	Front 5 m	gapixels with LED flash Jegapixels ²			
Disp	splay	5.5" HD + 720 (W) x 1440 (H), Transmissive IPS LCD	, outdoor visibility, optically bonded to Touch Panel			
Tou	uch Panel	Corning® Gorilla® Glass , Capacitive touch with stylus or bare or gloved fingertip input, multi-touch CTP water proof support water rejection and wet finger				
Physical Characteristics	eractive Sensor	Light sensor, Proximity sensor, Motion sensor (Accelerometer, G-sensor), E-compass (Magnetometer), Gyroscope				
Key	ypad	1 programmable key, volume up and down keys, left and right trigger keys, power key				
Auc	dio	Speaker, microphones with echo and noise cancellation				
Size	e (LxWxH)	165 x 76.8 x 17.9 mm				
	eight	288 g (with battery)				
	perating Temperature	-20°C to 50°C / -4°F to 122°F				
	orage Temperature	-30°C to 70°C / -22°F to 158°F (Without battery)				
Hun	imidity (non-condensed)	Operating 10% to 90% / Storage 5% to 95%				
User Environment	pact Resistance	IP65 & IP67, 500 tumbles at 0.5 m Standard: 1.5 m (5 ft.) multiple drops onto concrete, 6 drops on each side With rubber boot: 1.8 m (6 ft.) multiple drops onto concrete, 6 drops on each side				
Elec	ectrostatic Discharge	± 15 kV air discharge, ±	± 8 kV contact discharge			
Reg	gularity Compliance	CE, FCC, IC, NCC, TBL, JRL, SRRC, CCC, BIS,	WPC, WEEE, RoHS, REACH, CA65, BC, NrCAN			
Development Support		Android 10.0 SDK, reader API, SAM API, HTML 5 API				
Application Software	ReaderConfig, ButtonAssignment, Mobile Deployment Suite, Software Trigger Key, Xamarin Binding, CipherLab TE, AppLock, HTML5 (Browser and API), SOTI MobiControl, Kalipso, AirWatch, ReMoCloud, HF RFID Configuration, Signature Capture, SIP Controller, BT Printer Mate, Enterprise Setting					
Accessories	Charging and communication cradle, USB snap-on cable, Hand strap, Rubber boot, Pistol grip, 4-slot battery charger, Multi-slot Terminal charging cradle² , UHF RFID reader², Vehicle cradle²					
Warranty	1 year					

1. Minimum 12 hours under WLAN and 2D scanning per 20 seconds, LCD 50% backlight and speaker on (volume is default) at 25°C, RFID off / Bluetooth® off / IEEE 802.11 a / b / g / n /ac on. The test is based on one broadcasting packet per second.

2. Please contact us for availability.



@2021 CipherLab Co., Ltd. All specifications are subject to change without notice. All rights reserved. All brand, product and service, and trademark names are the property of their registered owners.